



DM 3600/3601

Enhanced Display Mobile Radios



- 1 Accessory connector supports USB and enhanced audio capability.
- 2 Multi-colored LED indicators for clear, visible feedback of calling, scanning and monitoring.
- 3 Large, easy-to-use volume knob.
- 4 DM 3601 includes integrated GPS module.
- 5 160 channels.
- 6 Powerful, front-projecting speaker.
- 7 Large, easy-to-use navigation buttons allow easy access to intuitive, menu-driven interfaces.
- 8 Flexible, menu-driven interface with user-friendly icons or two lines of text for ease of reading text messages.
- 9 Four programmable buttons for easy access to favourite features. New features such as one-touch calling and text messaging are made even easier through programmable button access.
- 10 Compact and ergonomically friendly microphone.

Display Mobile Radio Standard Package

- Radio with Display Control Head
- Trunnion
- Cabling (power cord)
- Compact Microphone
- Quick Reference Guide

Additional Features

- Enhanced call management
 - Encode/decode: emergency, remote monitor, push-to-talk ID, radio check, all call, radio disable
- DM 3601 can transmit GPS coordinates
- Dual-mode analogue/digital scan - facilitates a smooth migration from analogue to digital
- Short free-form and quick text messaging

MOTOTRBO™ System Components and Benefits

DM 3600/3601 Enhanced Display Mobile Radios

Specifications

GENERAL SPECIFICATIONS

Channel Capacity	160
Typical RF Output	
Low Power UHF and VHF	1-25 W
High Power UHF	25-40 W
High Power VHF	25-45 W
Frequency	136-174 MHz 403-470 MHz
Dimensions (HxWxL)	51 x 175 x 206 mm
Weight	1.8 kg
Current Drain:	
Standby	0.81 A max
Rx @ Rated Audio	2 A max
Transmit	1-25W: 11.0A max 25-40W: 14.5A max 25-45 W: 14.5A max

RECEIVER

Frequency	136-174 MHz 403-470 MHz
Channel Spacing	12.5 kHz/ 20/25 kHz
Frequency Stability	+/- 1.5 ppm (DM 3600) (-30° C, +60° C, +25° C)
Analogue Sensitivity	0.30 uV (12 dB SINAD) 0.22 uV (typical) (12 dB SINAD) 0.4 uV (20 dB SINAD)
Digital Sensitivity	5% BER: 0.3 uV
Intermodulation	70 dB
Adjacent Channel Selectivity	60 dB @ 12.5 kHz, 70 dB @ 20/25 kHz
Spurious Rejection	70 dB
Rated Audio	3 W (Internal) 7.5 W (External - 8 ohms) 13 W (External - 4 ohms)
Audio Distortion @ Rated Audio	3% (typical)
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Audio Response	+1, -3 dB
Conducted Spurious Emission	-57 dBm

MILITARY STANDARDS

Applicable MIL-STD	810E		810F	
	Methods	Procedures	Methods	Procedures
Low Pressure	500.3	II	500.4	II
High Temperature	501.3	I/A, II/A1	501.4	I/Hot, II/Hot
Low Temperature	502.3	I/C3, II/C1	502.4	I/C3, II/C1
Temperature Shock	503.3	I/A, 1C3	503.4	I
Solar Radiation	505.3	I	505.4	I
Rain	506.3	I,II	506.4	I, III
Humidity	507.3	II	507.4	-
Salt Fog	509.3	I	509.4	I
Dust	510.3	I	510.4	I
Vibration	514.4	I/10, II/3	514.5	I/24
Shock	516.4	I, IV	516.5	I, IV

TRANSMITTER

Frequency	136-174 MHz 403-470 MHz
Channel Spacing	12.5 kHz/ 20/25 kHz
Frequency Stability	+/- 1.5 ppm (DM 3600) (-30° C, +60° C, +25° C)
Power Output	
Low Power UHF and VHF	1-25 W
High Power UHF	25-40 W
High Power VHF	25-45 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 4 kHz @ 20 kHz +/- 5.0 kHz @ 25 kHz
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz
Adjacent Channel Power	-60 dB @ 12.5 kHz -70 dB @ 20/25 kHz
Audio Response	+1, -3 dB
Audio Distortion	3%
Digital Vocoder Type	AMBE+2
Digital Protocol	ETSI-TS 102 361-1, 2 & 3

GPS

Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)	
TTFF (Time To First Fix) Cold Start	< 1 minute
TTFF (Time To First Fix) Hot Start	< 10 seconds
Horizontal Accuracy	< 10 meters

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Temperature Shock	Per MIL-STD
Humidity	Per MIL-STD
Water and Dust Intrusion	IP54, MIL-STD

For more information please contact your local Motorola Authorised Dealer or Distributor



MOTOROLA and the Stylised M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2006. All rights reserved. Conforms to ETSI TS 102 361 (Parts 1, 2 & 3) - ETSI DMR Standard. Specifications subject to change without notice. MOTOTRBO will be launched with a phased introduction - please check availability of products in your region before ordering. All specifications shown are typical. Radio meets applicable regulatory requirements.

DM3600/3601/SPEC-ENG(01/07)

www.motorola.com

Motorola, Ltd. Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire, RG22 4PD, UK